according to 1907/2006/EC. Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Akepox 5010 Component B

10671, 10673, 22913, 10685B, 10686B, 10684B, 10687B, 11460B, 11461B, · Article number:

No further relevant information available.

11462B, 11463B, 11464B, 11465B, 11466B, 11467B, 11468B, 11469B, 11470B

· UFI: N1AA-2R3V-FY04-TGPT

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the

Epoxy resin adhesive mixture

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Laboratory

Lechstrasse 28 D 90451 Nürnberg Fax. +49(0)911-644456 e-mail info@akemi.de

Tel. +49(0)911-642960

AKEMI®

· Further information obtainable

1.4 Emergency telephone

number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m. National Poison Inform. Centre Medical Toxicology Unit Avalonley Road London SE14 5ER

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage. Skin Sens. 1 H317 May cause an allergic skin reaction.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin · Response:

with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Store locked up. Storage:

Store in a well-ventilated place. Keep container tightly closed.

· 2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 · Hazard pictograms

The product is classified and labelled according to the CLP regulation.

GHS07 GHS05

· Signal word Danger

· Hazard-determining components of

1,3-Cyclohexanedimethanamine labelling:

2,2,4-trimethylhexan-1,6-diamine

· Hazard statements H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

1 111ting date 04.12.2020	V 01 0	IOII HUITIDEI Z	11C VISIO11. 04. 12.2020
Trade name: Akepox 5010 Compo	nent B		
			(Contd. of page 1)
· <u>Precautionary statements</u>	P101	If medical advice is needed, have pr hand.	
	P102	Keep out of reach of children.	
	P103	Read carefully and follow all instruct	ions.
	P260	Do not breathe vapours.	
	P280	Wear protective gloves/protective cl protection/hearing protection.	othing/eye protection/face
	P303+P361+P3	53 IF ON SKIN (or hair): Take off imm clothing. Rinse skin with water [or sh	
	P305+P351+P3	38 IF IN EYES: Rinse cautiously with value Remove contact lenses, if present rinsing.	water for several minutes.
	P310	Immediately call a POISON CENTE	R/doctor.
	P333+P313	If skin irritation or rash occurs: Get n	nedical advice/attention.
	P501	Dispose of contents/container in regional/national/international regula	
· 2.3 Other hazards			
· Results of PBT and vPvB assess	sment		
· <u>PBT:</u>	Not applicable.		
· <u>vPvB:</u>	Not applicable.		

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-0000	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	12.5-25%
CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-xxxx	1,3-Cyclohexanedimethanamine Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312 Aquatic Chronic 3, H412	<10%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-xxxx	2,2,4-trimethylhexan-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1, H317	<10%
· Additional information:	For the wording of the listed hazard phrases refer to section 16	

<u>Additional information:</u> For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· After inhalation:

4.1 Description of first aid measures

· General information: Take affected persons out into the fresh air.

Position and transport stably in side position.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident. Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a

doctor.

· After swallowing: Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

(Contd. of page 2)

· <u>Information for doctor:</u> Amines: Inhalation, swallowing or dermal contact may cause health damages.

Cause burns, harm respiratory tract, eyes, skin, and digestion system in worst case up to complete destruction. Intermediate interferences such as headache, nausea, cough, dyspnea may occur. May cause allergies. Sensitized users may react towards very low amine concentrations and should avoid any further

contact with this group of chemicals.

 4.2 Most important symptoms and effects, both acute and

delayed

Headache Dizziness Nausea

Breathing difficulty

Coughing

· Hazards

Danger of impaired breathing.

• 4.3 Indication of any immediate medical attention and special

treatment needed

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· <u>Suitable extinguishing agents:</u> Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from

the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO) Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

· Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device. Do not inhale explosion gases or combustion gases.

· <u>Additional information</u> Collect contaminated fire fighting water separately. It must not enter the sewage

system.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Dispose of the material collected according to regulations.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and

explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

· Information about storage in one

common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

· Further information about storage

conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

· Storage class: 8 A

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

0.1 mg/l (MW)

· 8.1 Control parameters

· Additional information about design

of technical facilities:

No further data; see item 7.

Ingredients with limit values that require monitoring at the

workplace:

The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

values that have to be monitored at the workplace.		
· DNELs		
100-51-6	Benzyl alcohol	
Oral	DNEL (Kurzzeit-akut)	20 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	4 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	40 mg/kg bw/day (ARB)
		20 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	8 mg/kg bw/day (ARB)
		4 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	110 mg/m³ Air (ARB)
27 mg/m³ Air (BEV)		
DNEL (Langzeit-wiederholt) 22 mg/m³ Air (ARB)		
		5.4 mg/m³ Air (BEV)
2579-20-6 1,3-Cyclohexanedimethanamine		
Inhalative DNEL (Langzeit-wiederholt) 0.00947 mg/m³ Air (ARB)		
PNECs		
100-51-6	Benzyl alcohol	
PNEC (wä	issrig) 39 mg/l (KA)	

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

(Contd. of page 4) 1 mg/l (SW)

2.3 mg/l (WAS)

PNEC (fest) 0.456 mg/kg Trockengew (BO)

0.527 mg/kg Trockengew (MWS) 5.27 mg/kg Trockengew (SWS)

2579-20-6 1,3-Cyclohexanedimethanamine

PNEC (wässrig) 10 mg/l (KA)

0.003 mg/l (MW) 0.033 mg/l (SW)

25513-64-8 2,2,4-trimethylhexan-1,6-diamine

PNEC (wässrig) 0.01 mg/l (MW)

0.102 mg/l (SW)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic

measures:

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Short term filter device: Respiratory protection:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Preventive skin protection by use of skin-protecting agents is recommended.

· Protection of hands: After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Skin protection agent recommendation for preventive skin shelter without use of protective gloves:

STOKO EMULSION (http://www.stoko.com)

Skin protection recommendation for skin cleaning after product handling:

Kresto Člassic (http://debstoko.com)

Skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

(Contd. of page 5)

application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell,

internet: http://www.kcl.de).

· Material of gloves Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior

to the application.

· Penetration time of glove material Value for the permeation: Level \leq 6, 480 min

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are

suitable:

Butyl rubber, BR

Butoject (KCL, Art No. 897, 898)

Nitrile rubber, NBR

Dermatril (Art_No. 740, 741, 742)

· As protection from splashes gloves made of the following materials are

suitable:

Nitrile rubber, NBR

Dermatril (KCL, Art_No. 740, 741, 742)

· Not suitable are gloves made of

the following materials:

Leather gloves

Strong material gloves

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Appearance:

Form: Pasty Colourless Colour: Odour: Characteristic

· pH-value: Not applicable

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 205.4 °C

101 °C · Flash point: · Ignition temperature: 435 °C

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

1.3 Vol % Lower: 13 Vol % Upper:

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

		(Contd. of page 6)
· Vapour pressure at 20 °C:	0.1 hPa	
· Density at 20 °C:	1.07 g/cm³	
· <u>Solubility in / Miscibility with</u> <u>water:</u>	Partly soluble.	
· <u>Viscosity:</u> Dynamic at 20 °C: <u>Kinematic:</u>	8,000 mPas Not determined.	
· <u>Solvent content:</u> Organic solvents:	23.2 %	
· 9.2 Other information	No further relevant information available.	

Strong exothermic reaction with acids.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with strong oxidising agents. · 10.4 Conditions to avoid No further relevant information available. No further relevant information available.

10.5 Incompatible materials:

· 10.6 Hazardous decomposition

products: Corrosive gases/vapours

700 mg/kg (rat)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

Based on available data, the classification criteria are not met. · Acute toxicity

LD/LC50 values relevant for classification:				
ATE (Acut	te Toxicity	Estimates)		
Oral	LD50	2,437 mg/kg		

LD50 6,268 mg/kg Dermal Inhalative LC50/4 h 47.5 mg/l (rat)

100-51-6	Benzy	lalcohol

LD50

Oral

100 01 0 20112). 41001101		
Oral	LD50	1,040 mg/kg (mouse)
		1,040 mg/kg (rabbit)
		1,620 mg/kg (rat)
	NOEL	400 mg/kg (rat)
	NOAEL	200 mg/kg (mouse)
		400 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/8h	1,000 ppm (rat)
	LC50/4 h	11 mg/l (rat)
	LC50/48h	360 mg/l (daphnia magna)
		645 mg/l (goo)
2579-20-6	1,3-Cyclo	hexanedimethanamine

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

		(Conta. or page 1)
	LD0	>300 mg/kg (rat)
	LD100	2,000 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)
25513-64-8 2,2,4-trimethylhexan-1,6-diamine		
Oral	LD50	910 mg/kg (rat)
	LC50/48h	174 mg/l (Leuciscus idus)

· Primary irritant effect:

Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation May cause an allergic skin reaction. · Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met. · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure Based on available data, the classification criteria are not met. · STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard

SECTION 12: Ecological information

· 12.1 Toxicity . Aquatia taviaitu

· <u>Aquatic toxicity:</u>		
100-51-6 Be	nzyl alcohol	
EC50/24h	55-400 mg/l (daphnia magna)	
EC50/96h	640 mg/l (Scenedesmus pluvialis)	
EC50	2,100 mg/l (BES) (OECD 209)	
	79 mg/l (Scenedesmus quadricauda)	
EC10/16h	658 mg/l (pseudomonas putida)	
EC50/48h	230 mg/l (daphnia magna) (OECD 202)	
EC0	640 mg/l (Scenedesmus quadricauda)	
EC50/16h	658 mg/l (pseudomonas putida)	
EC50/30min	71.4 mg/l (Photobac. phosphoreum)	
	400 mg/l (pseudomonas putida)	
IC5/96h	640 mg/l (Scenedesmus quadricauda)	
NOEC	310 mg/kg (Pseudokirchneriella subcapitata)	
NOEC/21d	51 mg/l (daphnia magna) (OECD211)	
EC50/72h	770 mg/l (green alge) (OECD 201)	
	770 mg/l (Pseudokirchneriella subcapitata)	
LC50/96h	645 mg/l (goo)	
	10 mg/l (lepomis macrochirus)	
	460 mg/l (Pimephales promelas)	
2579-20-6 1,	3-Cyclohexanedimethanamine	
EC50	>1,000 mg/l (BES)	
	90 mg/l (pseudomonas putida)	
EC50/48h	65.4 mg/l (daphnia magna)	
ErC50/72h	>100 mg/l (Pseudokirchneriella subcapitata)	
LC100/96h	180 mg/l (Leuciscus idus)	
NOELR/72h	14.4 mg/l (Pseudokirchneriella subcapitata)	
	(Contd. on page 9)	

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

(Contd. of page 8)

EC50/72h 58.4 mg/l (selenastrum capricornutum)

LC50/96h 130 mg/l (Leuciscus idus)

EBC50 58.4 mg/l (Pseudokirchneriella subcapitata)

25513-64-8 2,2,4-trimethylhexan-1,6-diamine

EC50/24h 31.5 mg/l (daphnia magna)
EC50 89 mg/l (pseudomonas putida)
IC50 89 mg/l (pseudomonas putida)

ErC50/72h 37.1-43.5 mg/l (Pseudokirchneriella subcapitata)

NOELR/72h | 16 mg/l (Pseudokirchneriella subcapitata)

NOELR/21d | 1.02 mg/l (daphnia magna)

EC50/72h 29.5 mg/l (Scenedesmus subspicatus)

12.2 Persistence and

degradability
No further relevant information available.

12.3 Bioaccumulative potential
No further relevant information available.

· 12.3 Bioaccumulative potential · 12.4 Mobility in soil

No further relevant information available.

· Additional ecological information:

· <u>General notes:</u> Do not allow undiluted product or large quantities of it to reach ground water,

water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous

for water

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable. · vPvB: Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to

reach sewage system.

· European waste catalogue

20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND

INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS

20 01 00 separately collected fractions (except 15 01)

20 01 27* paint, inks, adhesives and resins containing hazardous substances

· Uncleaned packaging:

Recommendation: Empty contaminated packagings thoroughly. They may be recycled after

thorough and proper cleaning.

· Recommended cleansing agents: Alcohol

acetone

SECTION 14: Transport information

UN1719
1719 CAUSTIC ALKALI LIQUID, N.O.S. (2,2,4-
trimethylhexan-1,6-diamine, 1,3-
Cyclohexanedimethanamine)
CAUSTIC ALKALI LIQUID, N.O.S. (2,2,4-trimethylhexan-
1,6-diamine, 1,3-Cyclohexanedimethanamine)

(Contd. on page 10)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B	
	(Contd. of page 9)
· 14.3 Transport hazard class(es)	
· ADR	
· <u>Class</u> · <u>Label</u> · IMDG, IATA	8 (C5) Corrosive substances.
· Class	8 Corrosive substances.
· <u>Label</u>	8
· <u>14.4 Packing group</u> · <u>ADR, IMDG, IATA</u>	II
· 14.5 Environmental hazards: · Marine pollutant:	No
 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category Segregation Code 	Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG22 Stow "away from" ammonium salts SG35 Stow "separated from" SGG1-acids
14.7 Transport in bulk according to Annex II of Marpo	
and the IBC Code	Not applicable.
Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 Transport category Tunnel restriction code 	2 E
· <u>IMDG</u> · <u>Limited quantities (LQ)</u> · <u>Excepted quantities (EQ)</u>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1719 CAUSTIC ALKALI LIQUID, N.O.S. (2,2,4-TRIMETHYLHEXAN-1,6-DIAMINE, 1,3-CYCLOHEXANEDIMETHANAMINE), 8, II
	(Contd. on page 11)

AKEMI®

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

(Contd. of page 10)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances -

ANNEX I None of the ingredients is listed.

· REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic

equipment - Annex II

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· VOC EU

249.0 g/l

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for alterations

Relevant phrases H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Recommended restriction of use refer to Technical Data Sheet (TDS)

Department issuing SDS:Contact:LaboratoryElke Hake

Fon ++49 (0)911 64296-59

@mail E.Hake@akemi.de

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral – Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 12)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.12.2020 Version number 2 Revision: 04.12.2020

Trade name: Akepox 5010 Component B

(Contd. of page 11)

Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

Adaptation in accordance with REACH directive 1907/2006/EC